

Trusted, fully featured Windows<sup>®</sup> 10 platform, completely familiar for ease of operation.

Powerfull processing, long life battery and large memory: All day use, no concerns over data storage or performance.

Large, bright, all-weather display: All conditions, no compromise.

Rugged design: Focus on efficiently performing the job.

# ST100 tablet, Wherever the work takes you.

The Spectra Geospatial® ST100 is a hard working, no-nonsense tablet with a slim, rugged design and powerful features to handle any job. Whether your day includes a simple GIS workflow or a survey in a tough location, this reliable, versatile tool is up to the task.

The easy to read, scratch resistant touchscreen display, including LED backlight is a dependable high-performer in any environment. The ST100 is reliable and easy to operate. With a fully featured Windows® 10 platform, exceptional processing power, long battery life, 512 GB solid state drive and 16 GB SDRAM memory, you can work quickly and efficiently, without stopping for a recharge. And when the day is done, you can send your work to the office via 4G LTE, Wi-fi or Bluetooth® connection.

ST100, for the all-day performance you need - whatever the task.





# ST100 TABLET

# STANDARD FEATURES

- System
   Intel® Core™ i5 Processor
- Intel HD Graphics 620
   16 GB RAM¹
- 512 GB Storage<sup>2</sup>
- 10.1" 800 nits 1920 x 1200 (16:10) LED-backlight screen with capacitive multi-touch EMR Pen support
- 8 Megapixel camera with LED Flash
   Wi-Fi 802.11ac

- Bluetooth® v 5.1
   4G LTE WWAN EM7565
- Internal battery 92Wh non removable
- Integrated speaker and microphone
  IP65 Dust and Moisture Ingress Protection

**Operating System**• Microsoft® Windows® 10 Professional

# Communications

- · 4G LTE worldwide coverage, certified on Verizon and AT&T
- Wi-Fi 802.11ac
- Bluetooth v 5.1 USB 3.1 Type C x 2
- Supports USB C DisplayPort Alt Mode

## Standard Accessories

- Wacom Digitizer for EMR Pen Support
- AC-DC power adapter with power cord
   Screen protector
- USBA to USB C adapter

# **Optional Accessories**

- EMR Stylus and replacement tips and removal tool
   Handstrap
- Vehicle Power Supply
   Office stand
- · Pole mount (Short and long versions)

# TECHNICAL SPECIFICATIONS

# **Physical**

- Size
- 279 mm x 200 mm x 18.5 mm (11 in x 7.9 in x 0.7 in)
- Weight
- 1.65 ka (3.6 lbs.)
- Processor
- Intel® Core™ i5
- Memory
   16 GB SDRAM
- Storage 512 GB SSD
- User Interface
- Power button, directional pad, programmable function keys
   Power / Battery Status LED, On screen keyboard
- Battery
- 92Wh internal non removable
- Battery life 10 hours @ 20° C with GPS on
- Charging time

nduct Models

- 1:15 to 50% 3 hours to 100%3

### **Environmental**

- Operating temperature
   -20 C to +55 C (-4 F to 131 F)
   MIL STD 810H Method 501.7, 502.7 Procedure II

- Storage

   40 C to +70 C (-40 F to 158 F)
   MIL STD 810H Method 501.7, 502.7 Procedure I
- Thermal Shock
- - 20 C and 60 C non-operating MIL STD 810H Method 503.7 Procedure I-C
- Humidity
   0% 95% non-condensing
   MIL STD 810H Method 507.6 Procedure II -
- Aggravated Cycle Water & Dust Proof
- IEC 60629 Edition 2 IP65
- Vibration/Shock Resistance
   MIL STD 810H Method 514.8 Procedure I Random Vibration
  - MIL STD 810H Method 514.8 Procedure II Loose Cargo Transportation
- Drop
- Tests include room temperature, -20 C, +60 C MIL STD 810H Method 516.8 Procedure IV Transit
- Chemical Exposure Contamination by Fluids
- MIL STD 810H Method 504.3 Procedure II
- Non Operating Altitude
   -30 C and 40,000 Feet
- MIL STD 810H Method 500.6 Procedure I
- · Operating Altitude
- 5 C and 30,000 Feet
- MIL STD 810H Method 500.6 Procedure II

# Input/Output

- Display
- LED backlight, scratch-resistant, auto rotate
- Size
   10.1" capacitive multi-touch with EMR
- Resolution
   1920x1200 px
- Brightness
- 800 nits
- Audio - Built-in microphone and speaker
- I/0
  - USB 3.1 type c x 2
- AC / DC Adapter
   AC 100~240 V, 50~60 Hz, DC 5 V, 9 V, 15 V, 20 V, 65 W
- USB C PD 65W
- Digital camera (rear facing)
   8MP with auto-focus
- Sensors
- E-Compass, Accelerometer,, gyroscope, ambient light sensor, proximity sensor
- 2x Trimble EMPOWER Module Bays

STING (AG LTF)

- Internal antenna: Beidou, Galileo, GLONASS, GPS L1 C/A, QZSS

rioduct riodeis	31 100 (WI-FI)	31100 (40 LIE)
WLAN (Wi-Fi)	Yes	Yes
4G Data	No	Yes
Memory Storage (SSD)	512 GB	512 GB
GNSS	Included	Included

9T100 (W;\_E;)

1 GB = 1,000,000,000 bytes

Total usable memory will be less depending upon actual system configuration.

Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other settings or preferences.

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments. Do not charge batteries in extreme hot environments.





Spektra a Trimble Company

www.spektra.it | info@spektra.it

Via Pellizzari 23/A, 20871 Vimercate (MB) Tel. +39 039 625051